AD

AD-E403 691

Technical Report ARWSE-TR-14028

PREFIX VERSUS POSTFIX IN C++

Tom Nealis

October 2015



U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

Weapons and Software Engineering Center

Picatinny Arsenal, New Jersey

Approved for public release; distribution is unlimited.

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement by or approval of the U.S. Government.

Destroy this report when no longer needed by any method that will prevent disclosure of its contents or reconstruction of the document. Do not return to the originator.

LINCL ASSIFIED

3110E (3311 1ED				
REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-01-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden to Department of Defense, Washington Headquarters Services Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.				
1. REPORT DATE (DD-MM-YYYY)	2. REPORT TYPE		3. DATES COVERED (From - To)	
October 2015	Final			
4. TITLE AND SUBTITLE		5a. CO	NTRACT NUMBER	
PREFIX VERSUS POSTFIX IN C++		5b. GRANT NUMBER		
		50 DD(OCDAM ELEMENT NI IMBED	

5d. PROJECT NUMBER

5e. TASK NUMBER

Tom Nealis 5f. WORK UNIT NUMBER 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 8. PERFORMING ORGANIZATION U.S. Army ARDEC, WSEC REPORT NUMBER Fire Control Systems & Technology Directorate (RDAR-WSF-M) Picatinny Arsenal, NJ 07806-5000 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSOR/MONITOR'S ACRONYM(S) U.S. Army ARDEC, ESIC Knowledge & Process Management (RDAR-EIK) 11. SPONSOR/MONITOR'S REPORT NUMBER(S) Picatinny Arsenal, NJ 07806-5000

12. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

6. AUTHORS

Many coders today do not take the time to consider the implications of the code they write. Not all code is created equal, and something as seemingly harmless as incrementing or decrementing via prefix instead of a postfix notation can have a considerable effect on performance. Modern day compilers can and do optimize certain common instances of code involving this notation, but it should not be relied upon in a well-developed and maintained code base

15. SUBJECT TERMS

Prefix decrement Prefix increment Postfix increment Postfix decrement 16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF 18. NUMBER 19a. NAME OF RESPONSIBLE PERSON ABSTRACT OF Tom Nealis **PAGES** 19b. TELEPHONE NUMBER (Include area a. REPORT b. ABSTRACT c. THIS PAGE SAR code) (973) 724-8048 U

Technical Report ARWSE-TR-14028

CONTENTS

	Page
Introduction	1
Methodology	1
Conclusions	3
Distribution List	5

INTRODUCTION

Compilers today have become very good at optimizing code that has not been written in the most efficient manner possible. Many coders often take this for granted and do not spend time concerning themselves with the performance of their code and mistakenly rely on compilers to detect and correct inefficiencies. One simple example of why coders should pay attention and not rely on compilers to do the thinking for them is when to use prefix or postfix in their code.

Most coders coming out of school today all know the basic difference between these two lines of code:

```
function(++variable);
function(variable++);
```

The basic difference is that the first function call will be sent an incremented variable, whereas the second one will receive the current value of the variable and then the variable will be incremented upon return from the function. So, many coders will be comfortable with that knowledge but not think there is any difference between the next two lines of code:

```
variable++;
++variable;
```

In the end, both of these lines of code will increment the variable, but the concern is how.

METHODOLOGY

In order to understand the difference between these two notations, what is produced by the complier must be discussed. Without optimization, the compiler must create a copy in order to accomplish a postfix increment or decrement. The prefix does not require this and is, therefore, more efficient. Most modern compilers can detect and optimize the simple cases like the cases involving basic built-in types. This should not be relied upon and it should be a habit to always use prefix unless specifically needed to postfix. Take for example the following code:

```
for(int i = 0; i < SomeNum; i++) { doAnything; }
```

Most college professors and books will show loops written in this way. So, coders that have seen loops mostly written in this way will continue to write them in the same fashion. It is not necessary to postfix increment for this loop. Even though most compilers will optimize this properly in most cases, this should always be written for loop:

```
for(int i = 0; i < SomeNum; ++i) { doAnything; }
```

So let's take a look at some assembly. Modern compilers will produce the following after they optimize this code:

```
; 22 :;
jmp
         SHORT $LN2@wmain
//postfix built in type
; 21 : for(auto i = 0u; i < 10000; i++)
         DWORD PTR _i$1[ebp], 0
mov
jmp
         SHORT $LN3@wmain
         eax, DWORD PTR _i$1[ebp]
mov
add
         eax, 1
         DWORD PTR _i$1[ebp], eax
mov
         DWORD PTR _i$1[ebp], 10000; 00002710H
cmp
         SHORT $LN1@wmain
jae
; 22 :;
jmp
         SHORT $LN2@wmain
```

As one can see, the optimized code is exactly the same. The following loops are an example of code that is a little trickier for the compiler to optimize:

```
auto& it = my_ints.begin();
while(it != my_ints.end())
  it++;

auto& it = my_ints.begin();
while(it != my_ints.end())
++it*
```

The variable 'it' is a vector iterator. The prefix and postfix increment line of code produces the following assembly code:

```
//iterator prefix
00F755E2 mov ecx, dword ptr[it]
00F755E5 call std::_Vector_iterator<std::_Vector_val<std::_Simple_types<unsigned int> > ::operator++ (0F711F9h)
00F755EA jmp wmain + 0EEh (0F7558Eh)

//iterator postfix
002E5A12 push 0
002E5A14 lea eax, [ebp - 17Ch]
002E5A1A push eex
002E5A1B mov ecx, dword ptr[it]
002E5A1E call std::_Vector_iterator<std::_Vector_val<std::_Simple_types<unsigned int> > ::operator++ (02E10FFh)
002E5A23 lea ecx, [ebp - 17Ch]
002E5A29 call std::_Vector_iterator<std::_Vector_val<std::_Simple_types<unsigned int> > ::operator++ (02E10FFh)
002E5A29 call std::_Vector_iterator<std::_Vector_val<std::_Simple_types<unsigned int> > (02E119Ah)
002E5A2E jmp wmain + 0EEh (02E59BEh)
```

As one can clearly see, the compiler was unable to optimize the postfix. It had to create the copy. Figure 1 displays how long it takes to run through the previous code for a certain number of iterations.




Figure 1
Prefix versus postfix - iterators

CONCLUSIONS

The C++ coders need to take the time to understand implications of the code that they create. Some of the most benign looking code can have a significant impact on the performance of a piece of software that can, in turn, affect the device/system that is running it. An easily addressable example of this is the prefix and postfix notation. A coder should always use prefix notation unless they have to use postfix.

DISTRIBUTION LIST

U.S. Army ARDEC ATTN: RDAR-EIK RDAR-WSF-M, T. Nealis Picatinny Arsenal, NJ 07806-5000

Defense Technical Information Center (DTIC) ATTN: Accessions Division 8725 John J. Kingman Road, Ste 0944 Fort Belvoir, VA 22060-6218

GIDEP Operations Center P.O. Box 8000 Corona, CA 91718-8000 gidep@gidep.org

REVIEW AND APPROVAL OF ARDEC TECHNICAL REPORTS

Prefix Vs. Postfix in C++ Title Thomas M. Nealis Author/Project Engineer		Date received by LCSD Report number (to be assigned by LCSD)			
Extension	Building	Author's/Project Engineers Office (Division, Laboratory, Symbol)			
PART 1. N	flust be signed before the report	can be edited.			
a.	The draft copy of this report has for editing.	been reviewed for technical accuracy and is approved			
b.	Use Distribution Statement A_X	, B, C, D, E, F or X for the reason			
	checked on the continuation of the	his form. Reason:Operational Use			
	Information Service (NTIS	the report will be released to the National Technical) for sale to the general public. Only unclassified reports mited or controlled in any way are released to NTIS.			
 If Statement B, C, D, E, F, or X is selected, the report will be released to the Defense Technical Information Center (DTIC) which will limit distribution according to the conditions indicated in the statement. 					
c.	The distribution list for this report	has been reviewed for accordacy and completeness.			
		Patricia Alameda			
		Division Chief (Date)			
PART 2. To	be signed either when draft repor	t is submitted or after review of reproduction copy.			
Th	is report is approved for publicatio	n. //			
		Patricia Alameda 9/9/5 Division Chief (Date)			
		Andrew Pskowski			
		RDAR-CIS (Date)			